

	CONTACT	MAGNET	
TOP			<p>DESCRIPTION Grade 2, Class III triple pole angle contact. All poles NC (<i>Complete circuit when magnet present</i>). 1m armour sleeving + ~0.2m additional fly.</p> <p>ACTIVATION Reed switches, ~25mm operating gap.</p> <p>WIRING</p> <p>MATERIALS Anodised AA15 aluminium casting <- Ferrite/Alnico V magnet <- Rhodium reeds <- Stainless steel armour sleeving</p> <p>TEMPERATURE RANGE -40 to +50 degrees Celsius.</p> <p>ELECTRICALLY RATED AS FOLLOWS 100V / 500mA Max DC. 125V / 500mA Max AC.</p>
BOTTOM			
LATERAL			
LATERAL			
ENDS			
PHOTO			



KNIGHT
FIRE & SECURITY

Unit 84 Seawall Road Ind. Estate
Cardiff UK CF24 5TH
Tel: +44 (0) 2920 488 129
Fax: +44(0) 2920 489 132

Drawing #: H10TP
Drawn: Gareth Carpenter
Date: 01/03/2024
Revision: 1

All dimensions in mm
Do not scale



© Knight Fire & Security Products Ltd
All cases of infringement will be pursued.