



Fig. 1 – I10 Sounder / Extension Speaker



Fig. 2 – I20 Sounder / Extension Speaker

	Model			
	I10	I108	I20	I208
Grade 1 Class II	●	●	-	-
Grade 2 Class II	-	-	●	●
ABS Body	●	●	●	●
Resistor 16 Ohm	●	-	●	-
Resistor 8 Ohm	-	●	-	●
Micro-Switch	-	-	●	●
Surface Mounted	●	●	●	●

Concealed Fixings ● ● ● ●

Dimensions	Length	Width	Height
	120	120	50mm

Description:

Internal Sounder / Extension Speaker

Materials:

Body and Cover Plate - ABS

Temperature Range:

-40°C - +50°C

Tampers:

Microswitch

Speaker:

Diameter 87mm

Mylar – 16 Ohm, 12 Watt

Mylar – 8 Ohm, 12 Watt

Frequency range:

0.25-8Khz

Resonance:

550Hz ±110Hz

Sound Power Output

97dB

Voltage Range:

0-125v AC Max

0-200v DC Max

Colours:

I10 – I20 – White

Fittings:

Wire Clamping Terminals

Concealed Fixing Screws

KNIGHT

FIRE & SECURITY PRODUCTS LTD

email: info@knightplastics.com

Unit 84 Seawall Road Ind. Estate

Cardiff UK CF24 5TH

Tel: 0 (00 44) 29 20 48 81 29

Fax: 0 (00 44) 29 20 48 91 32

Drawing No: **I10-20
Sounders**

Drawn: *Chris Moorman*

Date: 11/02/08

All units in mm

Do not scale



© Knight Fire & Security Products Ltd
All cases of ™ Infringement will be pursued.