REAR VIEW SIDE VIEW FRONT VIEW DESCRIPTION Surface call point 70mm 32mm **POLES** 3mm ø 2—Double pole unit Common, N/O, N/C wiring on each pole as below **BACK** 0 Diagram shows call point in set, untriggered position BOX 87.5mm 85.5mm 70mm 87.5mm 85.5mm (a):::: 0 ::3.5mm ø **ACTIVATION** Microswitch/resettable plate Microswitch/"Like glass" insert 87.5mm Microswitch/Real glass insert 85.5mm Key provided WATERPROOFING None 68mm 53.5mm 10mm :★►: LED None **TEMPERATURE RANGE** WIRING TERMINALS 87.5mm 87.5mm **CALL POINT** 30mm 87mm 87mm **WIRING** 52mm 52mm -40 to +85 degrees Celsius **FRONT TERMINALS ELECTRICALLY RATED AS FOLLOWS** Max 50 Volts DC 50 Volts DC/5A 8mm ø 12.5 Volts DC/5A 250 Volts AC/3A 87.5mm 87mm 21.5mm



Unit 84 Seawall Road Ind. Estate Cardiff UK CF24 5TH

Tel: +44 (0) 2920 488 129 Fax: +44(0) 2920 489 132

Drawing #: MX74

Drawn: Gareth Carpenter

Date: 01/05/2016

Revision: 2

All dimensions in mm

Do not scale



© Knight Fire & Security Products Ltd All cases of infringement will be pursued.

NOTES REGARDING PART CODES:

The MX74 can be produced to various specifications. Use the below table as a guide on how the part code will affect the end product:

MX74	S/F	W/G/Y/B/R	S	С
	Surface	White		
		Green		With cover
	Flush	Yellow		If omitted: Without Cover
		Blue		
		Red		

EXAMPLES:

MX74SYSC: Double pole surface call point in yellow, resettable, with cover MX74SG: Double pole surface call point in green, like glass insert, no cover



Unit 84 Seawall Road Ind. Estate Cardiff UK CF24 5TH

Tel: +44 (0) 2920 488 129 Fax: +44(0) 2920 489 132

Drawing #: MX74

Drawn: Gareth Carpenter

Date: 01/05/2016

Revision: 2

All dimensions in mm Do not scale



© Knight Fire & Security Products Ltd All cases of infringement will be pursued.